# **MATERIAL SAFETY DATA SHEET**

Sorbent Fabric - White Oil-only

## **SECTION I: IDENTIFICATION OF PRODUCT**

**PRODUCT NAME:** Sorbent Fabric - White Oil-only (Apply for: White-Bonded, White-Laminated, and White-Fine Fiber) **CHEMICAL FAMILY:** Olefin **PRODUCT USE:** Sorbent Media **CHEMICAL NAME:** Polypropylene

#### MANUFACTURER'S NAME: Evolution Sorbent Products, LLC

#### **Manufacturing Location:**

1270 Nuclear Drive West Chicago, IL 60185

Emergency Telephone Number: 1-800-615-8699 Telephone Number for Information: 1-630-293-8055 Date Prepared: June 2011

## WORK PLACE HAZARDOUS MATERIAL INFORMATION SYSTEM(WHMIS)

WHMIS CLASSIFICATION: Not a Controlled Product under WHMIS WORK PLACE HAZARD: Not Applicable PRODUCT IDENTIFICATION NUMBER (PIN): Not Applicable

#### TRANSPORTATION OF DANGEROUS GOODS (TDG)

TDG CLASSIFICATION: Not Dangerous Goods PACKAGE GROUP: Not Applicable PRODUCT IDENTIFICATION NUMBER (PIN): Not Applicable

### **SECTION II: HAZARDOUS INGREDIENTS**

INGREDIENTS Polypropylene

# PERCENT CA 100% 900

<u>CAS NUMBER</u> 9003-07-0 OSHA PEL

ACGHI TLV

Not a Hazardous Material under WHMIS

#### SECTION III: TOXICOLOGICAL PROPERTIES HEALTH HAZARDS: (acute or chronic) None

SIGNS & SYMPTOMS OF EXPOSURE: None MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None

# **SECTION IV: FIRST AID MEASURES**

No special procedures required

# SECTION V: PHYSICAL DATA

APPEARANCE AND ODOR: SPECIFIC GRAVITY: BOILING POINT (C): MELTING POINT: SOLUBILITY IN WATER: PERCENT VOLATILE BY VOLUME: EVAPORATION RATE: VAPOR PRESSURE (mm hg):

White & virtually odor free 0.88-.092 Not Applicable >160°C Insoluble Not Applicable Not Applicable Not Applicable

# SECTION VI: FIRE AND EXPLOSION HAZARD DATA

 FLASH POINT: >329°C (625°F) (Setchkin test)

 FLAMMABLE LIMITS: Not Yet Determined

 EXTINGUISHING MEDIA: Water, Foam, CO<sup>2</sup>, Dry Chemical

 SPECIAL FIRE FIGHTING PROCEDURES: Standard procedures for class A fires

 UNUSUAL FIRE AND EXPLOSION HAZARDS: Some carbon monoxide formation is possible under oxygen-lean conditions. Sorbent product will not support combustion.

# **SECTION VII: REACTIVITY DATA:**

**STABILITY:** Stable (XX) **INCOMPATIBILITY (CONDITIONS TO AVOID):** None **INCOMPATIBILITY (MATERIALS TO AVOID):** Avoid contact with hot or concentrated nitric and perchloric acid, sulfuric acid or 98% sulfuric acid at 60°C or above. **HAZARDOUS POLYMERIZATION:** Will not occur. (XX)

# SECTION VIII: PREVENTIVE MEASURES/SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: None requiredVENTILATION:None requiredPROTECTIVE GLOVES:None requiredEYE PROTECTION:None requiredOTHER PROTECTIVE EQUIPMENT (SPECIFY): None required

# PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Store in a dry area. Do not store near open flame, high heat or strong oxidants. Polypropylene/synthetic fibers, when heated, become very sticky and will burn. Use self-contained air masks to enter smoky area in the event of fire.

## STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED

No special steps to be taken if material is spilled or released.

# WASTE DISPOSAL METHOD

Sanitary landfill or incineration site. Disposal must be done in accordance with local, state, and federal regulations.

# **SECTION IX: PREPARATION**

The data in this MSDS has been compiled from publicly available sources. This data relates only to the designated product and not to the use of said product in combination with other materials. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. All data in this MSDS is typical of the product as a whole, and does not represent any individual lot or batch, therefore, Evolution Sorbent Products makes no warranty about accuracy of the data herein and assumes no liability for the use of such data. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

DATE ISSUED: June 2011

PREPARED BY: Evolution Sorbent Products, LLC. Phone: 630-293-8055